

Final Design and Technologies for the IBIS 2.0

G. Viavattene¹, I. Ermolli¹, R. Cirami², G. Calderone², D. Del Moro³, P. Romano⁴, M. Aliverti⁵, V. Baldini², F. Giorgi¹, F. Pedichini¹, I. Coretti², P. Di Marcantonio², L. Giovannelli³, S. L. Guglielmino⁴, M. Murabito^{6,1}, L. Oggioni⁵, M. Oliviero⁶, R. Piazzesi¹, E. M. A. Redaelli⁵

¹INAF – OAR, ²INAF-OATs, ³Univ. Of Rome Tor Vergata, ⁴INAF – OACT, ⁵INAF – OAB, ⁶INAF - OAC


and with contributions by M. Munari, M. Stangalini, R. Briguglio and F. Landini



IBIS 2.0

- High resolution solar spectropolarimetric observations
- Upgrade and update the previous version of IBIS (DST from 2003 to 2019) planned for VTT in Spring 2023

[Cavallini (2006), Solar Physics, 236, 415-439]
[Ermolli et al. (2020), SPIE proceeding, 11447]




NEW

- Full automation of calibration and observation procedures (ESO VLT standard)
- Polarimetric Unit




Synergies:

- **INAF-OAR + INAF-OATs**: PI +PM
- **INAF-OAR**: reassembly in optical lab with a modified layout adapted for VTT
- **INAF-OAA**: dynamical optical aberration tests of critical components
- **INAF-OATs + INAF-OAR**: Instrument Control System hardware upgrade
- **INAF-OATs**: Instrument Control Software
- **INAF-OAR + INAF-OAC**: new polarimeter design
- **INAF-OACT + INAF-OAR**: science cases
- **INAF-OAR + INAF-OAB**: optomechanics
- **INAF-OAR**: detector trade-off





Polarimetric Unit: 6 modulation states

- Optical design and optimization with Zemax OpticStudio
- Fast 4Mpix sCMOS
- WFE characterization of LCVR with interferometer at INAF-OAA



Instrument Control

- New Instrument Control for a full automation of the calibration and observation procedures and remote access
- Beckhoff PLC with dedicated motors, actuators and stages
- First application of the ESO VLT Control Software to solar instrumentation





www.ibis20.inaf.it

Thank you for your attention