




Science Gateway Prototype

F. Tinarelli, C.Knapic, S. Bertocco, S. Zorba, G. Taffoni





Milano – ICT 2019






Actors: The Science Gateway





- The Science Gateway is the entry point of the data retrieval
- It is able to query the archive of observational data using standard VO queries
- It is usually dedicated to observational projects of one Organization
- If the syntax of the proposal_ID become a standard, it could serve observational projects of more Organizations







Actors: The Science Gateway Catalog



The catalog contains information encoded using IVOA notation. Group identifiers follow the GMS (current draft) specification, that embeds:

- > authority: managing the group management service
- service identification: to call for authZ purposes (The authN is not currently defined but it is being studied)
- > The group ID of the proposal dataset belongs to

Ivo://authority2.org/datalink?proposalID &filename ska_rc_demo_02.fits

cloud.src-it.inaf.it

ST.2022.1.00001.L

Science Gateway Catalog

IN: proposalD

OUT: Data Centre, files, IVO-ID


ivo://authority.org/path?groupID (ivo://auth.ska.org/grouper?ST_2022_1_00001_L)





Actors: The Remote Authentication Portal (RAP)





(Use the link https://rap.inaf.it/Services/DEMO to test a fully functioning demonstration.)


- RAP is an Authentication system built by INAF capable to handle multiple accounts for web application usage
- Born as a SKA Pre-construction phase component - a joint venture between Radio Astronomical Institute (IRA) and Italian Astronomical Archives (IA2)
- The first RAP prototype has been presented at the "SKA TM prototype strategy" meeting in Trieste in march 2015
- RAP is used in the production portal of IA2 in conjunction with Grouper since 2017
- The current RAP version is able to join the different user accounts into a single entity (Account Linking)
- RAP use OAuth2 and OpenID Connect to communicate with the Science Portal or other clients





Actors: RAP and Account Linking








Actors: RAP and the DEMO Customization





Each application that uses RAP can decide which functions to use among the available ones. The table below shows which options are enabled, you can change them to see what happens in RAP. Be careful that if you do not use LDAP and MariaDB, Join and Edit functions will be ignored.

Authentication Methods

eduGAIN:	oTrue ○False
OrcID:	oTrue ⊙False
X.509:	oTrue ○False
Local:	oTrue ○False
Google:	oTrue ○False
Facebook:	OTrue ○False
LinkedIN:	oTrue ⊙False
Registra	tion Methods
LDAP:	OTrue OFalse
MariaDB:	OTrue ○False
Register:	oTrue ○False
Join:	oTrue ○False
Edit:	OTrue OFalse



=	array (
	'manager'				t/xxxxx/Kkkkkk.php",
	'home'			tps://rap.inaf.i	
	'secret'				60t5667536tiugedgh",
	'client'			t5396089172hd",	
	'logo'			logo-200.png",	
	'gui'	=>	"/au	uth/devel/portal	/RAP.php",
	'edugain'	=>	true	э,	
	'orcid'		true		
	'google'				
	'facebook'				
	'linkedin'				
			true		
			true		
			true		
	'register'				
	'join'		true		
	'use_dbms'				
	'use_ldap'				
	'reg_field:	s' :			', 'mail', 'country'
					hone', 'mobile'],
					', 'mail', 'uniqid']
		=>	arra		
	'SP'			<pre>"https://xxxxx/</pre>	
				<pre>"https://xxxx/k</pre>	kkk.php"),
	'archive'				
	'dbms'			"mysql",	
	'db'			"database",	
	'host' 'user'			"localhost", "username",	
	'secre			"password"),	
	'ldap'		arra		
	'serve			"ldap://localho	et/".
				"cn=xxxxx, dc=ex	
				"password",	
	'dn'	-		"dc=example,dc=	ora",
	'versi	on'			
	'tls'			true));	

RAP is a Proxy between applications and identity providers or local registration

It can be customized from applications (through configuration file):

- Supported providers can be chosen
- Support for local user registration, and X.509 authentication
- It can be configured as pass-through authenticator without user registration
- LDAP and/or SQL Servers for user registration at first login (required for account linking) are supported
- LDAP and/or SQL Server DBs can be called locally by RAP or remotely
- RAP is Open Source. It can be installed as a local service or used as a network service









Actors: RAP the Config Command





- RAP Service Manager:
- Configure the layout of Service;
- Read Client ID and Secret;
- Add or Remove Authorized Redirect URI;
- Select The Service Logos;
- Select the Algoritm of JWT token and download the Public Key for RS256;
- Change the Top Page Images and Menu Icons;
- Manage SQL users and Align
 SQL and LDAP informations;



Exit

Submit

Manage: MySQL Users
Align DB








Actors: The Science Gateway GMS



ST 2022 1 00001 L/10001 53330313931303232f7ce4ea1@rap.inaf.it **Grouper/GMS** IN: groupID, user unique ID **OUT:** authorization Grouper Authorization

- The Group Management System contains information about the group that owns the requested proposal ID
- The group is defined by a group name (alphanumeric) and/or a group ID (numeric). Grouper uses only a numeric ID.
- If the Unique_ID of an authenticated user belongs to the group associated to the proposal_ID, then an authorization is issued.
- the authorization contains a group_ID and can contain a list of privileges associated with the unique_ID belonging to the group.









Token exchange with Science Gateway

Data Centre (Archive+Computation)

Token exchange


Data access and computation

Access to Data and Computational resources

Actors: The Data Centre



- > The Data Centre exchanges the authorization token with the Science Gateway.
- The token exchange (draft-ietf-oauth-token-exchange-16) is different from the access token used for user authentication. The token is signed with a new client_id and a new secret/keys.
- The Data Centre receives the information about data, groups, and user requests.
- > The Data Centre instantiates resources for data transfer or analysis.








The Prototype Step by Step (1)










The Prototype Step by Step (2)












The Prototype Step by Step (3)






Select the actions to manage your data





The Prototype Step by Step (4.1)












The Prototype Step by Step (4.2)









The Prototype Step by Step (4.2.1)





						X S	AOIma	ge d	ls9		
File Edit	Vie	w Frame B	in	Zoom Scal	e Co	lor Reg	ion W	VCS	Analysis	Help	
ile		ska_rc_demo	_01	fits							
Object		COMA36					X				
/alue		0.520142									
k5		12:59:19.9544	Ī	+27:54:35.695	Ī					E 🖌 X	0
'hysi cal	х	1038	Y	508	Ĩ						
mage	х	1038	Y	508	Î						
rame 1	x	1	Ī	0	•						




0.53



The Prototype Step by Step (4.3)












The Prototype Step by Step (4.3.1)


File



Login without password and analyze data



19/05



X SAOImage ds9

File Edit View Frame Bin Zoom Scale Color Region WCS Analysis Help

ska rc demo 01.fits






RAP and Grouper at INAF IA2 Archive



Remote Authentication Portal







Use the eduGAIN Logo to Login or Register to the RAP facility if you belong to an eduGAIN IdP.



Use these Logos to Login or Register to the RAP facility with your social identity



Use the X.509 Logo to Login with your personal certificate (IGTF and TERENA-TACAR, are allowed).



1 Need help? Please read our <u>User guide</u> and <u>FAQ</u>.

Privacy policy

RAP use two modified grouper connectors (Sonia Zorba IA2 staff) to authenticate PI as grouper administrator to manage group memberships of archived data files.







RAP and Grouper and the Account Linking



	Logged in as F	ranco Tinarelli (eduGAIN+Google+X.509) · Log						
Home								
Grouper								
This website allows you to manage groups as	ssociated with your organization and the men	nbers of those groups. For a list of answers to						
	Added attribute Unknown to a membership for member Franco Tinarelli (eduGAIN+Google+X.509). 2019/02/21 17:07 PM							
	X.509) as a member of the Unknown group.	2019/02/21 17:07 PM						
My favorites 🌣 View all favorites	Groups I manage	My services						
	Grouper Institute of Higher Educate This website allows you to manage groups at frequently asked questions, refer to the support Added attribute Unknown to a membership Added Franco Tinarelli (eduGAIN+Google+2) My favorites	 Home Garouper Institute of Higher Education This website allows you to manage groups associated with your organization and the ment frequently asked questions, refer to the support documentation. Recent activity Added attribute Unknown to a membership for member Franco Tinarelli (eduGAIN+Google Added Franco Tinarelli (eduGAIN+Google+X.509) as a member of the Unknown group. My favorites 						

Using the two modified connectors, grouper receives the joined identities (Account Linking) from RAP.






• INAF ISTITUTO MAZIONALE DI ASTROPHIYSICS MARY AND ALINSTITUTE FOR ASTROPHYSICS

Partner

design





Thanks for your attention!



Questions?



